

— Delta vfd-el parameter manual —

Скачать:

> [Delta vfd-el parameter manual](#)

Download:

> [Delta vfd-el parameter manual](#)

— Delta vfd-el parameter manual —

. Delta vfd-el parameter manual Some parameters settings can cause the motor to run immediately after applying power 3. VFD-B series is used only to control variable speed of 3-phase induction motors, NOT for 1phase motors or other purpose. Please read the wiring information in the user manual of brake unit thoroughly prior to taking into operation. To prevent personal injury, delta vfd-el parameter manual ensure that power has turned off before opening the AC motor drive and wait ten minutes for the capacitors to discharge to safe voltage levels. Failure to comply may result in fire, explosion or electric shock. Only use AC motor drives within specification. When the external input terminal NOTE The parameter can be set during operation for easy tuning. Frequency Proximity Sensor Activates Time Signal of Zero time between STOP and triggering by proximity sensor. In order to retain the warranty coverage, the AC motor drive should be stored properly when it is not to be used for an extended period of time. Check if the wiring of PG card is correct. Check parameter settings and signal type of PG feedback Pr. JOG PU Change between different display mode. For semiconductor components, damage will occur once any specification is out of range. In that case it starts up normally. It can be 1-phase or 2-phase input. Check Load current 2. The vibration effect is equal to the mechanical stress and it cannot occur frequently, continuously or repeatedly to prevent damaging to the AC motor drive. VFD-B series is used only to control variable speed of 3-phase induction motors, NOT for 1phase motors or other purpose. DO NOT install the AC motor drive in a place subjected to high temperature, direct sunlight, high humidity, excessive vibration, corrosive gases or liquids, or airborne dust or metallic particles. Revision July 2008, BE16, SW V4. Data Format For ASCII mode: 7. Delta vfd-el parameter manual Ye s Yes Yes Can dec elerati on Can ac celerati on time be made longer. Time or add an optional brake resistor and brake unit. If it exceeds the Maximum Allowable Power Loss Time, the AC motor drive output is then turned off coast stop. NOTE Make sure that RUN command or signal is OFF before executing RESET to prevent damage or personal injury due to immediate operation. Use inverter duty motor. Press STOP RESET key on PU01.